

DOCKET NO.: 0645-4034

PATENT

UNITED STATES PATENT APPLICATION

*BB*  
*for ALL*  
For  
*Apparatus for making a*  
RECLOSABLE DISPENSER PACKAGE,  
~~RECLOSABLE OUTLET FORMING STRUCTURE AND~~  
~~METHOD AND APPARATUS FOR MAKING SAME~~

by

Sanford Redmond

EXPRESS MAIL LABEL NO. EG296911528US

This non-provisional application claims priority to United States Provisional Application Serial No. 60/010,455, filed January 23, 1996, and United States Provisional Application entitled "RECLOSABLE DISPENSER PACKAGE, RECLOSABLE OUTLET FORMING STRUCTURE AND METHOD AND APPARATUS FOR MAKING SAME", filed January 3, 1997 by the same inventor of the instant non-provisional application, both of which are herein incorporated by reference.

FIELD OF THE INVENTION

This invention relates to easy opening, self-contained, easy to use, single or multiple use dispenser packages capable of economical, high speed production, manufactured from a broad range of materials, many of which are recyclable. They may contain such products as syrups, cream, cheeses, salad dressings, shampoo, hand-cream, liquid detergents, motor oil, toothpaste pates, pet food and many other products. It additionally relates to a package which has the capability of dispensing the contained product, e.g., mouthwash, cough syrup, confections, alcoholic beverages, etc., directly into the mouth of the user, and which also includes a reclosure cap member formed as an integral part of the package and which preferably is tethered to the package by a tether also formed integrally with the package. It will also be seen that the easy opening feature together with the reclosure cap and tether may be formed independently and sealed or adhered to the surface of many packages such as bags, milk containers, pouches, pillow packages (sachets), etc. to make for very efficient low cost dispensing packages or squeeze bags. These squeeze bag type packages could dispense food pastes such as pet food, cremes, grease, yogurt, certain types of dough, cake frosting and could be made of everything from treated, coated paperboard plastic films, foils, laminates or coextrusions of these

materials. The easy opening means of this application in its preferred embodiment is comprised of a drum-like protrusion from which a secondary frusto conical protrusion extends to create a tip which is encircled at its base by a fault line. To create the aperture this tip is broken away by applying light lateral finger pressure. In order to protect this breakaway tip during shipment or for reclosing the aperture, a tethered cap is also formed adjacent to the double protrusion. The tether functions not only to hold the cap, thereby preventing the cap from being lost, but also to hold the cap [on the tip] in place by acting like a spring.

In an alternate aperture forming system the initial drum like protrusion has, instead of a frusto-conical breakaway tip, a fault line pattern defined in its top surface, so designed as to rupture to create an outlet of various required shapes when a puncturing tool/plug is pressed into said fault line pattern. Such puncturing tool/plug may be formed instead of a cap and may be tethered or the cap may be double ended with a cap formation on one end and the puncturing tool/plug formation on the other. It will also be seen that a cap containing a protruding member formed within the cap similar to the style of a flower would perform as a central punch when the cap is pressed over the drum shaped protrusion. It will further be seen that in certain instances where a metal foil liner is required for a flowable product such as an alcoholic drink the drum shaped protrusion may be replaced by a moundlike protrusion with a central fault line pattern. The reason for such a moundlike shape instead of the drum shape is to prevent the stretching of the foil beyond its elastic limit at surface intersections in which case it would rupture during formation. Said pattern able to be punched open by a formed puncturing tool/plug said puncturing

tool/plug may be thermoformed and tethered to the unit or may be independently made and the tether may have a formed ring at its free end into which the puncturing tool plug may be seated.

5           This invention also relates to a method and apparatus for manufacturing the aforesaid formation and packaging, reliably at high speed, in many cases from fully recyclable material, so as to permit such packages to be produced at low cost and, in many cases, recyclable. 10 Additionally the packages may use less plastic material than most other previously known portion packages leading to source reduction and environmental benefits even when non-recyclable materials are used.

#### BACKGROUND OF THE INVENTION

15           Various attempts have been made to provide a dispenser package in which a product may be packaged in the quantity normally required for single or multiple uses, and from which the contained product may be dispensed.

20           One type of such dispenser packages is a pillow pouch or sachet, typically made of relatively thin plastics and foils or combinations of laminated plastics and foils. These packages are most frequently encountered as containers for catsup, mustard, other condiments, 25 homecare preparations such as hair conditioners, dyes and cremes, etc. Although this type of package is universally used, it is also universally disliked by the consumer. In order to access the contents, the pouch must be held in one hand while a tearing motion and force are applied by 30 the other hand. Creating the initial tear to break the packages seal is often very difficult, often requiring the assistance of the user's teeth. Moreover, once the initial tear is created, the laminated foil and/or plastic material not only often tears in an uncontrolled fashion, 35 but the holding pressure exerted by one of the user's

hands often forces the contents out of the envelope not only before the user is ready to apply the contents, but even before the tearing motion is complete. Opening these packages leads to frayed tempers, broken fingernails, and chipped teeth, as well as other problems. The user must also use both hands to open the container. In the case of invalids, arthritis sufferers and other handicapped people, opening these packages is virtually impossible. Yet another problem associated with these prior packages is the impossibility of efficient reclosure, thereby precluding multiple use of the package, with consequent waste of the unused contents. Further disadvantages include the sachet's inability to function effectively with low viscosity products such as coffee cream, mouthwash or alcoholic beverages, due to the inability of the torn opening to control the direction of flow of such liquids from the package. These packages also are generally totally unrecyclable, and therefore become environmental pollutants. As above-mentioned however, should continued use of these sachets be preferred, then the easy opening feature of this application may be readily and economically adhered to the sachet to make for an easy opening, reclosable, high-barrier package.

Another dispenser package is the peel-top cup used for butter, margarine, syrup, sauces, salad dressing, and other similar products. This type of package requires good eyesight and manual dexterity. Such packages are often used as coffee creamers and have many disadvantages, including difficulty in peeling off the top in order to open, as well as difficulty in pouring, accidental spilling, and the inability to be reclosed so as to preclude more than a single use. Again the inventions described herein can be adhered or integrally formed into these packages to make them easy opening and reclosable. Yet another type of dispenser package is the unsealed

corrugated paper package used for salt and/or pepper, which upon bending along an interrupted line cut through the corrugations forms an opening through which the salt or other material contained in the package may flow.

5 These packages only dispense dry, solid flowables with the assistance of gravity, and cannot be used to contain, no less dispense, "wet" or liquid flowable materials. The package of this invention can contain and readily dispense both liquids and dry granular products.

10 Small, very expensive, metal capped bottles are used for alcoholic drinks and are either poured or consumed directly from the bottle. These bottles may be reclosed, but often are sized for a single drink so they do not have to be reclosed. The instant package can be  
15 used for alcoholic beverages at a fraction of the cost of the bottles.

Everyone is familiar with the ubiquitous gable top milk carton and everyone is familiar with the varying degrees of difficulty in opening them. These range from  
20 fingernail breaking to just plain unopenable without a knife or other tool.

They never truly reclose and at best are messy and unclean looking. In the U.S. there has been a move toward mounting a screw-on cap combination comprising a  
25 threaded nozzle member which is sealed onto one of the slanted gables of the carton and the other is an unattached screw-on cap. This little injection molded duo is costly to make and to install, possibly on the order of 3 to 5 cents and is commonly used on large gable top juice  
30 containers in the half gallon size. These are expensive, high profit items selling for about three dollars each and can bear the extra tariff for the screw-on outlets. There are however billions of these gable top units sold annually for milk and cream in varying sizes from half-  
35 pints to half gallons. Producers however are reluctant to

increase carton cost significantly and the public continues to use difficult to open cartons.

5 The instant invention makes available a sealed and tamper evident outlet with a tethered cap, both formed in a single, small plastic unit which can be readily sealed or adhesively attached to the gable over a small pre-made hole. It is ultra low cost and may be made of polypropylene, high density polyethylene, PVC. Polyester etc. utilizing material costing small fractions of a cent. 10 It will be seen that the cap serves a double purpose. It enables the outlet to be reclosed after opening and of equal importance, since the cap is in place over the breakaway tip during shipment it protects the tip from being accidentally hit or subjected to any forces which may open the outlet. 15

20 It may be seen that the lower drum-like formation beneath the breakaway tip may be elongated so that when the tip is broken away, an elongated nozzle remains which would allow the flowable substance to be ingested directly from the container or as in the case of motor oil, being poured directly into the engine oil inlet. Another disadvantage currently experienced with dispensing packages is the closing of the outlet opening. Closing the outlet opening of tubes is presently 25 accomplished by means of an injection molded screw-on cap which normally includes a compressible gasketing material. The end of the tube requires a mating thread to match the cap. Both the separately molded gasketed cap and the threaded tube result in increased manufacturing costs. 30 Additionally, the cap, as often as not, is dropped and/or lost while it is being threaded on or off. Furthermore, there has been a growing trend to manufacture such tubes at still greater cost by providing hinged caps with a flat end surface which permits the tube to stand upright. 35 Thus, the cap members currently in use have the

disadvantage that they tend to increase the overall cost of manufacture of the dispensing package.

OBJECTS OF THE INVENTION

5 It is therefore an object of this invention to provide a new and improved means of creating an aperture in a thermoformable plastic material as well as an integrally formed cap and tether where necessary.

10 A further object is to form independently such aperture creating means with or without a cap and/or tether for adhesion to other forms of previously difficult to open or non-reclosable packaging.

Another object of this invention is to provide new and improved dispenser packages.

15 Another object of this invention is to provide a new and improved aperture-forming structure for a dispenser package which allows the user to easily and controllably dispense the contents of the package directly to the user's mouth or in a directionally controlled manner, as desired.

20 Another object of this invention is to provide a new and improved aperture-forming structure for a dispenser package which opens easily and reliably and yet which can be manufactured economically and at high speed.

25 Another object of this invention is to provide a new and improved reclosable dispenser package so that the contents thereof may be dispensed in consecutive uses and the outlet opening reclosed between uses.

30 A further object of this invention is to provide a new and improved reclosable package with an attached cap member formed from the same plastic film which cap member may be thereafter placed over the unopened aperture forming means to protect it and/or to reclose the package after opening.

35 Another object of this invention is to provide a new and improved reclosable package and removable cap



member which may be formed as an integral unit and where the cap member is attached to an integrally made tether and remains attached to the package and which may be placed over the unopened aperture forming means to protect it from changes or accidental opening during shipping and handling.

Another object of this invention is to provide a new and improved reclosable package and tethered cap member which may be formed as an integral unit from a thermoformable material.

Another object of this invention is to provide a new and improved reclosable package and tethered cap member which may be formed as an integral unit from a thermoformable plastic material that is recyclable.

Another object of this invention is to provide a new and improved dispenser package and cap member wherein the cap member has an open-ended top of predetermined shape so that, upon placing the cap over the aperture of the package the contents may be dispensed in such shaped stream.

Another object of this invention is to provide a new and improved dispenser package and cap member wherein the cap member includes a utensil device such as tiny protrusions or a flattened surface structure so that the cap member may function as a tool to brush, spread, or otherwise handle the contents dispensed from the package.

Another object of the invention is to replace the cap member with a dual function punch/plug member capable of punching through a tough pre-scored formation to create an aperture and to further act as a plug to close said aperture.

A still further object of this invention is to provide a new and improved method of making a dispenser package embodying the aforesaid features.

Another object of this invention is to provide a new and improved method of thermoforming a dispenser package from a recyclable plastic material at high speed and yet provide a finished package which may be easily and reliably opened by the user.

Another object of this invention is to provide a new and improved apparatus for forming an aperture-forming structure for a dispenser package.

Another object of this invention is to provide a new and improved apparatus for forming a nozzle-like aperture structure in a dispenser package so that, upon opening, the contents of the package may be dispensed in a directionally controllable manner.

Another object of this invention is to provide a new and improved self-centering and self-aligning punch and die apparatus adapted to accurately and reliably form a thermoformable material into a hollow tip-like configuration having a peripherally extending fault line so as to permit the tip to be readily broken away by the user to form an aperture opening through which the contents of the package may be dispensed.

The foregoing specific objects and advantages of the invention are illustrative of those which can be achieved by the present invention and are not intended to be exhaustive or limiting of the possible advantages which may be realized. Thus, these and other objects and advantages of the invention will be apparent from the description herein or can be learned from practicing the invention, both as embodied herein or as modified in view of any variations which may be apparent to these of ordinary skill in the art, the same being realized and attained by means of the parts, constructions and instrumentations, and combinations thereof, as well as in the steps and processes pointed out in the appended claims. The present invention resides in the novel parts,

constructions, arrangements, combinations, steps and processes, and improvements, herein shown and described.

SUMMARY OF THE INVENTION

5 Briefly described this invention is directed to  
a new reclosable aperture forming means which may be  
formed with an integrally formed cap member which may be  
tethered to said aperture forming means to create a unit  
which may be independently formed and adhesively or  
sealingly attached to a container wall or surface over a  
10 hole in said container wall to create an easy opening,  
reclosable, when necessary, dispensing package. Said  
reclosable aperture forming means embodying an integral,  
hollow protrusion member preferably comprised of two  
stages, a drum shaped base from which extends a generally  
15 conical or frusto-conical tip, said tip member having a  
fault line encircling it at its juncture with the flat top  
surface of the first drumlike formation which may be  
readily broken off to form an opening through which the  
contents of the package may be dispensed in a  
20 directionally controllable stream. After the tip of the  
protrusion member is broken off by applying light lateral  
finger pressure, the desired quantity of the contents may  
thereafter be expelled through the opened nozzle-like  
outlet by gentle hand squeezing of the package.

25 In a second embodiment the entire reclosable  
aperture forming means may be integrally formed into what  
will become an easy to use reclosable dispensing package.  
In this second embodiment a generally relatively flexible,  
compressible pouch or container member is sealably  
30 attached to a cover member forming the top or lid of the  
package. The cover member includes the new reclosable  
aperture forming means and tethered cap member as  
described above and similarly used.

35 In another desirable embodiment the pouch or  
container member has the integral hollow protrusion and

tethered cap member thermoformed into the underside of its relatively stiff rim. The advantage of this version being that the cover member then becomes a relatively thin skinlike member which is very easy to print and less expensive than the formed upper cover member.

The aforesaid cap member which is initially formed with the package as an integral unit is preferably formed along one peripheral edge of either the cover member forming the top or lid of the package relatively closely adjacent to the breakaway protrusion member or on the underside of the rim. A cut line may create a tether member which permits the cap member to be mechanically removed by the user from its molded position in production and placed over the opened nozzle-like aperture forming means so as to protect the breakaway tip during shipping and handling, while remaining tethered to the package. As also preferably embodied, the aforesaid cap member permits the end user of the package to readily open or reclose the package after each use.

\* \* \* \*

In other alternative embodiments of the dispenser package of the present invention:

(i) the breakaway protrusion member forming the aperture in the package may be broken off at the surface of the cover member forming the top or lid of the package, thereby eliminating the nozzle-like outlet configuration in those applications where the contents of the package don't require nozzle formation;

(ii) the cap member may be formed with miniature protrusions to act like a brush, or may have some other desired shape to perform some other desired tool function for use in handling the contents dispensed from the package, such as by brushing or spreading;

(iii) if reclosing the package is not required, the cap member may be open-ended having a predetermined

shape such that, upon placing the cap member over the nozzle-like aperture of the package, the contents may be dispensed in such shaped stream;

5 (iv) the cap member may be provided with an internal central plug dimensioned to mate with the opening formed in the dispenser package to thereby serve as a plug to further ensure sealing of the opening after removal of the breakaway protrusion member; and

10 (v) the breakaway protrusion and tethered cap members may be formed in a portion of the cover member which extends beyond one end of the compressible pouch member at a predetermined angle and communicates with the product contained in the pouch by means of a shallow neck or channel, thereby facilitating application of the  
15 contents of the package onto a surface, such as, e.g., toothpaste onto a toothbrush or glue onto a break line. Alternatively, the breakaway protrusion member may be formed in the cover member directly over the pouch portion with the cap formed at an adjacent small flat area. This  
20 method yields a somewhat larger pouch volume while using the same total amount of material.

It will be understood that the foregoing preferred embodiments of the dispenser package of the present invention may be thermoformed from a wide variety  
25 of plastic materials, including, e.g., PP (polypropylene) Barex, HDPE (high density polyethylene), HIPS (high impact polystyrene) and foamed HIPS, as well as various laminations and/or coextrusions of the aforesaid materials and other plastic materials, including, e.g., PP/EVOH  
30 (ethylene vinyl alcohol)/PP; Barex/PP; Barex/EVOH/PP; PET (polyethylene tetrafluoride)/LLDPE (linear low density polyethylene); PET/EVOH/LLDPE; PVC (polyvinylchloride)/LLDPE; NY (nylon)/LLDPE; and NY/EVOH/LLDPE. Alternatively, the aperture forming means

and the dispenser packages of the present invention may be formed by injection molding.

It also will be understood that the foregoing preferred embodiments of the dispenser packages of the present invention may be manufactured in a wide variety of sizes, as desired, although the preferred size range is from about 2 ml capacity to about 4 fluid ounce capacity. Similarly, the aforesaid package may be manufactured in a wide range of dimensions. A typical size for a package containing 30 ml or 1 fluid ounce of material is on the order of about 1 inch deep by about 1 inch wide by about 3 to 4 inches long, which fits comfortably in the palm of the hand of most users. Furthermore, the independent formations of aperture forming means and the tethered caps may be applied to a very wide range of packaged from single use sizes to half gallons.

Briefly described, as preferably embodied, the apparatus of the present invention forming the preferred aperture-forming protrusion member in the cover member of the dispenser package includes a two-stage punch member which advances to engage and clamp a thermoformable material against a self-centering and self-aligning hollow anvil member. The first punch member advances to initially form a hollow, drum-shaped protrusion in a specific heated area of the thermoformable material. Thereafter, a second punch member preferably located within, and moveable relative to, the first punch member continues to advance forward. The second punch member includes a first generally frusto-conically shaped surface adapted to form a substantially cylindrical or frusto-conically shaped hollow tip member extending from the drum-like protrusion formed by the first punch member. At the moment formation of the hollow tip member is completed, the forward advancement of the second punch brings a second shallow conical surface into cooperating

engagement with the peripheral edge or rim defining the hollow portion of the anvil member to thereby compress the wall of the formed hollow tip about a peripheral portion thereof to create a weakened fault line in the hollow tip protrusion member. As here preferably embodied, the aforesaid punch and anvil members create a fault line at the base of the aforesaid hollow tip protrusion member which extends continuously about the periphery thereof.

In an alternative embodiment of the apparatus of the present invention, the heated sheet of thermoformable material is clamped against the anvil member and a single stage punch member having a generally frusto-conically shaped forward end portion is thereafter advanced to form the aforesaid hollow, substantially cylindrical or frusto-conically shaped tip member. At the moment formation of the hollow tip member is completed, the rim of the anvil member compresses the wall of the hollow tip member about the periphery thereof to create a weakened fault line. It will be seen that the heated thermoformable film (material) may be clamped against a relatively thin plate spaced away from the anvil which contains an accurately aligned hole centered on the aperture of the anvil member. In this embodiment, between the punch and anvil the film will be formed into a conical member as the punch is advanced through the plate and said conical member will then be further formed until it contacts the peripheral edge or rim at the opening of the aperture in the anvil. This alternate apparatus creates a fault line banding or girdling the formed conically-shaped tip member at a predetermined point between its base and its apex.

It will be appreciated by those skilled in the art that the foregoing various brief descriptions and the following detailed description are exemplary and explanatory of the present invention, but are not intended to be restrictive thereof or limiting of the advantages

which can be achieved by the invention or various combinations thereof. The accompanying drawings, referred to herein and constituting in part hereof, illustrate preferred embodiments of the invention and, together with the detailed description, serve to explain the principles of the invention.

**BRIEF DESCRIPTION OF THE DRAWINGS**

FIG. 1 is a side elevation view of a dispenser package constructed in accordance with the present invention with an integrally formed cap member;

FIG. 2 is a top plan view of the dispenser package of Figure 1;

FIG. 2a is a perspective view of a dispenser package constructed in accordance with the present invention with an integrally formed cap member on the underside of the containment members rim and their skin like unformed cover member;

FIG. 3 is an end view of the dispenser package of Figure 1;

FIG. 3a is an end view of the dispenser package of Figure 2a showing an unformed very thin flexible cover member;

FIG. 4 is a side view in elevation, partly sectional, of an apparatus constructed in accordance with the present invention for forming the breakaway tip and nozzle protrusion members in a heated sheet of thermoplastic material;

FIG. 5 is an enlarged sectional view, partly in elevation, of the first and second punch members and the self-aligning hollow anvil member illustrated in FIG. 4, this view illustrating formation of the first protrusion member in the thermoplastic sheet material;

FIG. 6 is an enlarged view similar to FIG. 5, illustrating formation of the second protrusion member in the thermoplastic sheet material;



FIG. 7 is an enlarged view of FIG. 6, illustrating formation of the peripherally extending weakened fault line at the base of the second protrusion member;

5           FIG. 7a an enlarged side plan view of first and second protrusion members according to one embodiment of the present invention;

10           FIG. 7b is an enlarged side plan view of first and second protrusion members according to one embodiment of the present invention;

FIG. 8 is an isometric view of the dispensing package of Figure 1;

15           FIG. 9 is an enlarged isometric view of the dispensing package of Figure 8, illustrating the cap member removed from its molded position and placed over the breakaway tip protrusion member;

20           FIG. 10 is a schematic illustration showing the use of a hollow punch member for forming a central sealing plug member in the cap member illustrated in the preceding drawings;

FIG. 11 is an isometric view of a cap member formed with a central plug from the apparatus of Figure 10;

25           FIG. 12 is an enlarged cross-sectional view, partly in elevation, illustrating an alternative embodiment of the punch and anvil apparatus of the present invention, wherein a single punch member forms a hollow frusto-conical protrusion in the surface of the cover member for a dispenser package and the anvil member compresses the wall of the tip to form a peripherally extending fault line on the surface of the protruding tip;

30           FIG. 12a is an enlarged cross-sectional view, partly in elevation, illustrating an alternative embodiment of the punch and anvil apparatus of the present invention, wherein a single punch member forms a hollow

frusto-conical protrusion having a right-cylindrical base in the surface of the cover member for a dispenser package and the anvil member compresses the wall of the tip to form a peripherally extending fault line on the surface of the protruding tip;

FIG. 12b is an enlarged cross-sectional view, partly in elevation, illustrating an alternative embodiment of the punch and anvil apparatus of the present invention, wherein a single punch member having a spherical tip forms a hollow mound protrusion in the surface of the cover member for a dispenser package and the anvil member compresses the wall of the tip to form a peripherally extending fault line on the surface of the mound;

FIG. 13 is a schematic elevation view of the breakaway tip formed by the punch and anvil members illustrated in FIG. 12;

FIG. 13a is a schematic elevation view of the breakaway tip formed by the punch and anvil members illustrated in FIG. 12a;

FIG. 14 is a top plan view of another embodiment of a dispenser package constructed in accordance with the present invention, wherein the breakaway tip and cap member are formed in a lateral extension of the cover member and the breakaway tip member communicates with the containment pouch through a shallow channel member;

FIG. 15 is a side view of the embodiment illustrated in FIG. 14;

FIG. 16 is an end view of the embodiment illustrated in FIG. 14;

FIG. 17 is a side view of the embodiment of the invention illustrated in FIG. 14, wherein the lateral extension of the cover member also extends angularly downwardly;

FIG. 18 is a schematic view of an alternate embodiment of the cap member, formed with bristles or nubs on its outer surface;

5 FIG. 19 is a schematic view of another alternate embodiment of the cap member, formed with a flattened spreader tool utensil on its outer surface;

10 FIGS. 20a-d are partial end views of still other alternate embodiments of the cap member of the present invention, each view illustrating an open-ended cap member;

FIG. 21a is a top plan view of a reclosable outlet aperture forming structure which can be applied to various forms of containers in accordance with an alternate embodiment of the present invention;

15 FIG. 21b is a side view of the reclosable outlet aperture forming structure shown in FIG. 21a;

20 FIG. 22a is a perspective view of the reclosable outlet aperture forming structure of FIGS. 21a-b, as applied to a milk carton, in which the cap is placed over the outlet;

25 FIG. 22b is a perspective view of the reclosable outlet aperture forming structure of FIGS. 21a-b, as applied to a milk carton, in which the cap is removed from the outlet so as to allow removal of the breakaway outlet tip;

FIG. 22c is a perspective view of the reclosable outlet aperture forming structure of FIGS. 21a-b, as applied to a milk carton, in which the breakaway tip is removed from the outlet to form an opening therethrough;

30 FIG. 22d is a perspective view of the milk carton of Figures 22a-c, in which the breakaway tip is removed from the outlet to form an opening through which milk is being poured;

FIG. 23 is a side view of a low profile breakaway tip in accordance with another embodiment of the present invention;

5 FIG. 23a is a side view of a low profile breakaway tip in accordance with another embodiment of the present invention;

FIG. 24 is a top view of the low profile breakaway tip of FIG. 23;

10 FIG. 24a is a top view of the low profile breakaway tip of FIG. 23a;

FIG. 25 is a perspective view of the low profile breakaway tip of FIG. 23 with the removed breakaway tip shown in phantom;

15 FIG. 26 is a side view of a cap for use with the low profile breakaway tip of FIG. 23;

FIG. 27 is a side view of a another embodiment of the present invention which utilizes a twist-lock or twist-threading arrangement to secure the cap to the base formation;

20 FIG. 28a is a perspective view of another embodiment of the present invention in which a tethered plug is used to open and close a pre-scored surface;

25 FIG. 28b is a perspective view of the embodiment of FIG. 29a in which the pre-scored surface has been opened;

FIG. 28c is a perspective view of the embodiment of FIG. 28a in which the plug has been placed in the outlet hole, thereby opening the hole along the pre-scored surface and/or plugging the hole;

30 FIGS. 29a-d are top views of the outlet of the embodiment of FIG. 28a depicting various types of scored surfaces formed in the outlet; and

FIGS. 30a-d are side views of the scored surfaces shown in FIGS. 29a-d, in which each of the scored

surfaces have been penetrated to create an opening therethrough and a flap descending from the surface;

5 FIG. 31 is a partially elevated side view of an outlet forming structure according to an alternative embodiment of the present invention, having a punch/plug and a scored mount, as applied to a milk carton;

FIG. 32 is a top plan view of the outlet forming structure of Figure 31;

10 FIG. 33 is a side plan view of the outlet forming structure of Figures 31 and 32;

FIG. 34 is an enlarged elevated view of the outlet forming structure of Figures 31-33;

15 FIG. 35 is an enlarged side plan view of the outlet forming structure of Figures 31-34 showing the mound as punctured by the punch/plug;

FIG. 36 is an enlarged side plan view of the mound of Figures 31-35;

20 FIG. 37 is a side plan view of an alternative embodiment of the present invention in which an outlet forming structure, having a breakaway tip and cap, is applied to a foil package;

FIG. 38 is an enlarged side elevational view of the outlet forming structure of Figure 37;

25 FIG. 39 is an elevated plan view of an alternative embodiment of the present invention as applied to a foil package;

FIG. 37a is a side plan view of an alternative embodiment of the present invention in which an outlet forming structure is applied to a foil package;

30 FIG. 38a is a front plan view of the outlet forming structure of Figure 37a;

FIG. 39a is an elevated plan view of the outlet forming structure of Figures 37a and 38a;

35 FIG. 40 is a partial elevational view of an outlet forming structure according to another alternative

embodiment of the present invention, having a snap-in auxiliary punch/plug/cap and protrusion member, that is manufactured by a pick-and-place method;

5       FIG. 40a is an enlarged side plan view of the outlet forming structure of Figure 40 showing the punch/plug/cap puncturing the protrusion member;

10       FIG. 41 is a top plan view of an alternative embodiment, wherein the outlet forming structures are formed from a single thermoplastic web in a mating arrangement;

15       FIG. 42 is a side plan view of an alternative embodiment of the present invention in which the reclosable container is provided with a scored protrusion and a dual purpose tethered punch/cap;

20       FIG. 43 is a top plan view of the reclosable container of Figure 42;

25       FIG. 44 is a top plan view of the reclosable container of Figures 42 and 43, wherein the tethered punch/cap is securely fastened over the scored protrusion;

30       FIG. 45 is an elevated plan view of an outlet forming structure according to one embodiment of the present invention;

35       FIGS. 46a-c are side plan views of a container for use with an outlet forming structure according to the present invention;

40       FIG. 47 is an elevated plan view of the container of Figures 46a-c with the outlet forming structure of Figure 45 mounted thereon;

45       FIG. 48 is a top plan view of a container according to an embodiment of the present invention;

50       FIG. 49 is a side plan view of the container of Figure 48;

55       FIG. 50 is a side plan view of the container of Figures 48 and 49 in a closed position;

FIG. 51 is a side perspective view of the container of Figures 48-50;

FIG. 52 is a side elevational view of a container according to an embodiment of the present invention;

FIG. 53 is an enlarged side plan view of the outlet forming structure of Figure 52; and

FIG. 54 is a top plan view of a section of a web of thermoformable material having a series of outlet forming structures formed therein.

DETAILED DESCRIPTION OF VARIOUS PREFERRED EMBODIMENTS

Referring now more particularly to FIGS. 1-4 and 9 of the accompanying drawings, there is illustrated a dispensing package indicated generally at 10 according to the present invention. The package 10 can be used for single or multiple uses and can be reclosed for further use.

As illustrated in FIGS. 1 and 4, the package 10 includes a cover member 11 formed from a flexible but relatively stiff generally flat sheet 12 of a thermoformable plastic material most suitable to the product contained and the protection that the contained product requires.

Materials such as high-impact polystyrene (HIPS), high density polyethylene (HDPE) polyester, HDPE/EVOH (high density polyethylene/ethylene vinyl alcohol), Barex, polypropylene, etc. may be used. HIPS, HDPE, and HDPE/EVOH are each low cost and can be recycled. HDPE/EVOH creates a superior O<sub>2</sub> barrier.

As will be understood by those skilled in the art, whereas plastics of similar material may be heat-sealed or bonded together, heat sealing different plastics together requires an adhesive layer. Preferably, linear low density polyethylene (LLDPE) is used as such a layer. Thus, multi-layered plastics formed by coextrusion may be

sealed together to form sheet 12 having sealant/barrier 14 of the present invention.

Also suitably bonded to one face of bonded sheet 12, 14 is a flexible sheet 18 forming at least one pouch chamber 22 adjacent one face of the relatively stiff sheet 12 or bonded sheet 12, 14 for containing a preferably flowable substance, e.g. a dry powdered or granulated material or a liquid material of any suitable viscosity capable of flowing under light to moderate hand pressure.

Advantageously, and as here preferably embodied, the layer of a suitable sealant/vapor impervious barrier material 14 is suitably integrally bonded to sheet 12 on the inner surface 16 which faces flexible sheet 18. Flexible sheet 18, advantageously formed by conventional means, such as vacuum forming, pressure forming, mechanical forming or combinations thereof, is likewise suitably integrally bonded to either inner surface 16 or sealant/barrier 14 of sheet 12, as the case may be.

The bonds between substantially flat relatively stiff sheet 12, sealant/barrier material 14 and flexible sheet 18 also may be formed by conventional means known to persons of ordinary skill in the packaging art, such as welding, heat sealing, or adhesive or cohesive bonding. It will be understood that the particular bonding method selected depends upon the particular properties of the materials used and the flowable substance(s) to be contained in the package.

Advantageously, and as preferably embodied, sheet 12 is preferably made of polypropylene (PP), Barex, high impact polystyrene (HIPS) or high-density polyethylene (HDPE), but when combined with barrier 14 may be made of polystyrene, polyester, EVOH (ethylene vinyl alcohol), polyvinyl chloride (PVC), polyethylene tetrafluoride (PET) or nylon, or a copolymer thereof, and barrier 14 is made of a suitable sealant/vapor impervious



barrier material, preferably comprising saran and foil laminate, or comprising a laminate of foil and vinyl, or foil alone, depending on the nature of the contents to be contained.

5 A particularly tough high barrier construction comprises saran laminated on each side with polyethylene (sold by Dow Chemical Co. under the name "Saranex") as barrier sheet 14, in turn laminated onto polystyrene or polyester, forming the flexible but relatively stiff sheet 10 12. The thickness of sheet 12 varies according to factors, such as the properties of the materials used, the flowable substance contained, and the intended usage. A generally utilized range is 4-12 mils (0.004-0.012"). As previously noted, sheet 12 preferably is somewhat 15 flexible, although more rigid than the material 18 forming pouch 22, and preferably is stiffened by raised portion 11a formed in cover 11 in the preferred construction of package 10.

20 It will be understood by those of ordinary skill in the art that the bonds formed between materials 12, 14 and 18 can be obtained by the conventional means previously described, again depending on the nature of the flowable substance being contained.

25 It will be seen from the foregoing that the structure of FIGS. 1 and 2 forms an enclosed pouch or chamber 22 between the flexible sheet 18 and the relatively stiff member 12, 14 in which a preferably flowable substance is contained and from which the contained substance is dispensed.

30 ~~In accordance with the present invention as preferably embodied, the relatively stiff generally flat sheet 12 forming cover 11 includes an aperture-forming protrusion structure 30 which includes a neck member 32 and a breakaway tip member 34 so that, upon removal of tip 35 34, neck 32 forms a nozzle-like aperture in package 10~~

through which the contents may be dispensed in a directionally controllable manner.

5  
10 Neck and tip protrusions 32, 34 preferably are substantially hollow, substantially cylindrical and tip 34 preferably is substantially cylindrical or frusto-conical. In the preferred embodiment as shown in the plan view of Figure 3, the aperture-forming protrusion structure 30 is located in cover 11 directly over pouch 22 so that, when opened, nozzle aperture 32 communicates directly with the contents of pouch 22.

15 In accordance with the present invention, as preferably embodied, dispenser package 10 includes a cap member 110 formed as an integral part of cover 11. Advantageously, cap member 110 is removable from cover 11 along a line.

20 It will be seen that the cap 110 protects the breakaway tip structure 30 from inadvertently breaking off during shipping and handling prior to use, as well as providing a means to reclose the package after opening, i.e., after the protrusion tip member 34 is broken off. Thus, cap 110 protects the remaining contents of the package after each use, permitting multiple uses. The advantage of the tethered embodiment of the invention is that it costs practically nothing, acts as a side pressure spring to maintain the cap on the neck 32 at the opening, acts as a grasping member to assist removal of the cap for each subsequent use, and prevents loss of the cap before the contents of the package have been fully dispensed and the package is ready to be disposed of. Further details of the cap are explained below.

25  
30 In practically all cases, however, it is believed preferable to provide the two-stage breakaway tip configuration since the first projecting cylindrical formation 32 acts as a nozzle yielding directionally  
35 controllable product dispensation, after the tip, i.e.,

second protrusion 34, is broken off. Low and medium viscosity flowable products tend to squirt "side-ways" or spurt in non-controllable directions, when passing through an aperture formed in the plane of the cover member. Furthermore, elevating the breakaway tip from the surface of the cover member greatly enhances its ease of use with no practical increase in manufacturing cost.

In use, as here preferably embodied, package 10 preferably is positioned so that pouch or chamber 22 rests in the palm of the hand with the thumb resting on the cover 11. The thumb or finger of the holding hand, or the user's other hand, if desired, may then be used to apply a light finger pressure against the side of protrusion tip 34, i.e., the breakaway tip, thereby causing tip 34 to break off, leaving an open neck or nozzle-like aperture

32.

Once tip 34 is removed and the package thereby opened, the contents of the package 10 may be expelled. This method of use depends on the type of substance contained in the package and where the user would like to place the contents. For example, if the package contains toothpaste, the open nozzle 32 preferably would be placed over a tooth brush, whereupon gentle squeezing of the package 10 will force the toothpaste onto the toothbrush. If the contents of the package are intended to be placed directly into the user's mouth, or the mouth of a patient, such as for oral medicine or mouthwash, the open nozzle 32 then may be placed directly into the mouth and a portion, or all, of the contents may then be directed into the mouth by squeezing the package. When the desired quantity of the contents of the package has been expelled, if some contents remain, package 10 may then be reclosed for future use by placing cap 110 over the open nozzle 32.

As previously mentioned, as here preferably embodied, package 10 further includes a cap 110. While

cap 110 may be formed separately from the other elements of package 10, in the preferred embodiment cap 110 is integrally formed with and is at least partially detachable from the relatively stiff sheet 12 forming cover 11, as shown in FIGS. 1-3, 9-10, 15-18, 22-23d, 29a-c, 32-35, 38-40, and 42-47, for example.

As shown in Figs. 1-3 and 8-9, cap 110 preferably is located at one corner in cover 11 so as to overhang pouch 22. A cut line 114 allows cap 110 to be easily removed from cover 11. Advantageously, as best seen in Fig. 10, cut line 114 extends only partially along the edge of cover 11 so as to provide a tether 130 to maintain cap 110 attached to package 10 even after the cap is placed over either the aperture-forming structure 30 or over the open nozzle 32.

Cap 110 typically is unthreaded and is dimensioned to fit smoothly, yet securely, over the necked protrusion 32, which preferably also is smooth and unthreaded, both before and after removal of tip 34. Cap 110 has a base 126 which lies flat against the top of cover 11. Tether 130 has several advantages. First, it has been discovered that the tether 130 acts as a spring pressing the cap against the sidewall of the necked protrusion 32, thereby assisting to hold cap 110 in place when it is placed over the necked protrusion 32. Additionally, tether 130 provides the added benefit of preventing the cap 110 from becoming lost and allows the user to grip the tether 130 to assist in removal of the cap 110 from the aperture-forming structure 30 or from open nozzle 32.

Cap 110 of the present invention can be designed in several different embodiments. For example, in the embodiment shown in Figures 10 and 11, the cap can be formed from a hollow punch member 120 that forces the

material into a hollow female member 122 with a central protrusion 124 to form a cap with a central plug 126.

5 An alternative to the embodiment shown in Figs. 1-4 is shown in Figs. 2a and 3a. As shown, the container 10a has generally the same configuration as container 10 depicted in Figs. 1-3 is made of the same materials. Specifically, pouch 22a is formed between a flexible sheet 18a and the very thin skin like sheet 12a, 14a, in which a flowable substance is contained. Unlike the previous  
10 embodiment, the aperture-forming protrusion structure 30a is formed on the underside of the flat sheet 18. Similarly, the cap 110a is formed on the underside of the sheet 18. With such an arrangement, not only are the neck and tip protrusions 32a, 34a of the protrusion structure  
15 30a protected from accidental rupture, but also the container 10a is provided with a low cost flexible cover. In order for the protrusion structure 30a to be in fluid communication with the contents of the pouch 22a, the pouch 22a is provided with a channel 11b which  
20 communicates with the protrusion structure.

50B/17  
It will be understood that the aperture-forming protrusion structure 30 may be made by a variety of methods and apparatus. In accordance with the present invention, however, as preferably embodied, a web of thermoformable material to be formed into cover 11 is first heated to a sufficient forming temperature. The web is then formed into the hollow cylindrical protrusion 32 with a closed end. The closed end portion of the cylinder  
30 32 is then further deformed in its central section to create the tip 34. At the moment tip 34 is completely formed, the intersection of the base of tip 34 and cylinder 32 is compressed, reducing its thickness, to thereby create a fault line extending about the periphery of the base of tip 34.

Also in accordance with the present invention, as here preferably embodied, aperture-forming protrusion 30 is formed by means of a self-centering and self-aligning male and female punch and die apparatus, indicated generally at 40, as shown in Figs. 4-7.

Apparatus 40 includes feed rollers 42 or other means to advance the web or film "F" of thermoformable material into a heating station 44 where a heater block 46 advances against the film to press the sheet against a stationary heater block 48, which is temperature controlled by a thermocouple 50 and supplied with necessary power at connection 51. An air cylinder 52 provides the driving force to move the heater block 46 by means of shaft 54. The heater block 46 includes two heaters energized by an appropriate power source 58.

A two-stage punch member 60 includes a first male punch 62 formed as a generally cylindrical hollow punch having a substantially flat end surface 64 at its operative end. When the first punch member is advanced, the end surface 64 engages and deforms the heated sheet of thermoformable, preferably plastic, material F, compressing the plastic against a similarly shaped, oppositely mounted, generally cylindrical hollow anvil member 66 movable in a bore 68 of a support 70. The anvil 66 has an end face 71. The first punch 62 has a clearance fit with the bore 68 so it can be moved therein to confront the end face of the anvil 66. Anvil 66 has an aperture bore 67 formed as part of its hollow portion.

Anvil 66 is part of a spring-loaded rocker member 72, preferably supported by a ball-shaped member 74, or other similarly shaped curved rocker device, in a larger base opening 75 so as to be both resilient and self-centering and self-aligning with punch member 60. Although rocker 74 is preferably curved or ball-shaped, a relatively flat surface in spring-mounted engagement with

the base of adjustable mechanism 89 also serves to self-center the aperture opening 67 of anvil member 66 with respect to frusto-conical surface 84 and bevelled surface 83 of second punch 80, more fully described hereinafter.

5 The peripheral edge or rim of aperture 67 in anvil 66 is smaller than the bore of punch 62 to create an internal shoulder 76 when the opposing substantially flat end surfaces 64, 71 of the hollow cylindrical punch member 62 and the anvil member 66 are brought together. The anvil  
10 and first punch are preferably made of hardened steel.

In use, at the end of the first stage of the formation of the aperture-forming protrusion 30, shown in Figure 5, the plastic web F is formed into a projecting, closed end, hollow generally cylindrical drum-like shape,  
15 with the plastic web stretched across the end of the first generally cylindrical hollow punch, and clamped between the opposed facing end surfaces 64, 71 of the punch and anvil members.

A second punch member 80 is mounted for travel within a hollow bore 81 and beyond the end face 64 of the  
20 first punch member 62. The second punch member 80 includes a shaft 82 whose operative end surface includes a shallow bevel 83, advantageously on the order of 45°, terminating into a conically-shaped portion 84 with a flat end face 85 forming a frusto-conically shaped tip,  
25 indicated generally at 86. The second punch member and its bevel 83 advances into controlled engagement with the internal peripheral edge of the shoulder 76 formed at the opposed end surfaces 64, 71 of the first punch 62 and  
30 anvil 66.

In one aspect of the present invention, as preferably embodied, the second punch member 80 can be constructed in multiple parts. For example, each of the frusto-conical and beveled portions 84, 83 may be formed  
35 separately and removably attached to the leading end

surface of the shaft 82, such as by threaded connections. Alternatively, shaft 82 and tip portions 83, 84 may be formed as an integral unit. The second punch member is driven by air cylinder 87.

5 It will be understood from the foregoing that the full length of the frusto-conical end 86 of punch 80 continues to travel past the formed internal shoulder 76 and into the anvil aperture 67 until such time as bevel surface 83 is brought into accurately controlled  
10 cooperating engagement with the internal peripheral edge of the internal shoulder 76 formed by the opposed end surfaces 64, 71 of the first punch 62 and the anvil 66. Advancement of punch surface 83 against shoulder 76 is accurately controlled by micrometer punch adjustment  
15 mechanism 88 and anvil adjustable stop mechanism 89.

20 ~~The still-heated closed end of the initially formed hollow cylinder 32, i.e., the first drum-like protrusion of the aperture-forming structure 30 is, in a second stage, further formed into a substantially cylindrical or frusto-conically shaped tip 34, i.e., the second protrusion of the aperture-forming structure 30, by the advancing second punch member until the shallow bevelled surface 83 of punch 80 engages the plastic sheet. At that time, the second punch surface 83 controllably  
25 compresses, cools and sets the plastic web F against the internal peripherally extending edge formed at shoulder 76 of the anvil to reduce the thickness, and thereby weaken, the wall of the plastic at the locus of the peripheral edge so as to form a narrow, peripherally extending indentation 100, known as a rupture or fault line, at the  
30 base of tip protrusion 34. It will be seen that fault line 100 permits the tip protrusion 34 to be readily broken away by means of only light lateral pressure to thereby form a nozzle-like outlet opening at neck  
35 protrusion 32.~~



It should be noted that changes in the dimensions of the beveled end 86 and the anvil 66 are within the scope of the present invention. For example, it is often desirable to produce a fine stream of the contents of a container, such as motor oil. Consequently, the opening formed by the base of the tip protrusion 34 must be relatively small, such as shown in Fig. 8a. To form such a aperture-forming protrusion structure 30, the end 86 is elongated, and the beveled surface 83 is positioned closer to the distal end 85. Furthermore, the anvil 66 is provided with a relatively narrow opening. Consequently, as shown in Fig. 7a, the fault line 100 and the breakaway tip 34a are smaller. Alternatively, the entire punch 82 and, therefore, protrusion structure 30 is made narrower.

In other applications, where the contents of a container are large particles, such as cat food, the opening must be relatively large, such as shown in Fig. 7b. To achieve a larger opening, the entire punch 82 and, therefore, protrusion structure 30 are made wider. Alternatively, the fault line 100 and the break away tip 34 are made larger.

In an alternate embodiment illustrated in Figures 12 and 13, a single punch 90 with a truncated end 92 can be used. The single punch 90 includes a bevelled surface 94 which engages the film or web F of thermoplastic material to form the generally frusto-conical hollow tip protrusion 34. As here embodied, thermoplastic web F is first clamped between shoulder plate 96 and face 97 of an outer punch member similar to punch 62. Thereafter, punch 90 advances, whereupon end 94 forms web F into frusto-conical tip 34, as shown as Fig. 13. As alternatively embodied, however, as best seen in Fig. 12, upon completion of the formation of tip 34, the peripheral edge 76a of anvil member 70 engages and

compresses the outer surface of the frusto-conical wall of tip 34 to create a peripherally extending fault line 100a along the projecting surface of tip 34 between its base and apex.

5 In yet another alternative embodiment illustrated in Figs. 12a and 13a, a single punch 91 with a beveled, truncated end 93 can be used to form the generally frusto-conical hollow tip protrusion 31. The single punch 91 engages the film or web F of thermoplastic material with the beveled surface 93. As with the  
10 embodiment shown in Figs. 13 and 14, the thermoplastic web F is first clamped between stop plate 95 and clamp means 98 of an outer punch member. Thereafter, punch 91 advances, whereupon end 93 forms web F into the frusto-conical tip 31. As best shown in Fig. 13a, contact of the peripheral edge 77 of angle member 71 compresses the outer surface of the frusto-conical tip 31 to create a peripherally extending fault line 100b. In contrast to the embodiment shown in Figs. 12 and 13, the stop plate 95  
15 is situated adjacent the shaft of the punch 91, below the beveled, truncated end 93. Consequently, the thermoplastic web F is formed around the beveled end 93 as well as the right cylindrical shaft 91a. As can best be seen in Fig. 13a, the resulting frusto-conical tip 31 has a breakaway tip 35, a permanent projection 33, and a bright cylindrical section 33a. The right cylindrical section 33a is provided so a cap may be securely engaged with the tip 31.

20 In an alternative embodiment illustrated in Figure 12b, a single punch 91B has a spherical tip 93A. The spherical tip 93A engages the thermoplastic web F to form a hollow mound protrusion. As embodied, the thermoplastic web F is first clamp beneath a stop plate 95A. Thereafter, punch 91B advances, whereupon the  
25 spherical end 93A forms web F into a hollow mound.

Furthermore, the punch 91B is advanced forwards anvil 71A until the outer surface of the web F engages the peripheral edge 77A of anvil member 71A, thereby creating a fault line that extends around the tip of the mound structures. It has been found that the spherical tip 93A allows for self alignment of the punch 91B as the web F engages the peripheral edge 77A of the anvil 71A.

Referring now more particularly to Figs. 15-18 of the accompanying drawings, there is illustrated an alternate embodiment of the dispenser package of the present invention, indicated generally by reference numeral 200. As here embodied, cover 211 includes a lateral extension 211a which extends beyond one end of the container pouch 222 and both the aperture-forming structure 230 and reclosure cap member 240 are formed in cover extension 211a. A shallow channel member 250 communicates aperture-forming structure 230 with the contents of pouch 222. Further alternatively, as shown in Fig. 17, lateral extension 211a of cover 211 is formed on an angle with respect to cover 11 so as to slope toward the pouch side of cover 11.

It has been found that the embodiments of Fig. 14-17 are advantageous in that they facilitate dispensing the contents of the package onto a surface, such as butter or cream cheese onto a slice of bread or toothpaste onto a toothbrush.

Referring now more particularly to Figs. 18-20, there are shown several other alternative embodiments of the cap member of the present invention. Thus, as shown at Fig. 18, the top of resealing cap 110 may include bristles or nubs to function as a brush member; as shown in Fig. 19, the top of cap 110 may have a flattened surface 270 capable of functioning as a spreading tool; as shown in Figs. 20a-d, cap 110 may be open-ended and have a shaped edge configuration, such as shown at 280, 281, 282,

283, respectively, so that the contents of the package may be expelled in a shaped stream.

With reference to Figures 21a-b and 22a-c, an alternate embodiment of the present invention will now be shown and described. In accordance with this alternate embodiment, an independent thermoformed unit is used to create an outlet aperture in a container. The independent thermoformed unit may take the form of a reclosable outlet forming structure 300. The reclosable outlet forming structure 300 may generally comprise a cap 310, a tether 320, a base 330, and a breakaway outlet tip 340. Cap 310 may be connected to base 330 via tether 320. Score 325 facilitates separation of the cap 310 from structure 300. The reclosable outlet forming structure 300 may have a pre-applied adhesive or sealant in the area surrounding the base 330 to facilitate application of the structure 300 to a container, such as milk container 302. As such, the structure 300 may be sealably or adhesively attached to any surface of a container requiring the subject outlet. In particular, the structure 300 may be sealed or adhered to the container in an area surrounding a hole in the container, but not in the area of the cap 310 or tether 320 which must be free of the container's surface. It is to be understood that reclosable outlet forming structure 300 may be attached to containers, such as milk carton 302, prior to filling. As such, the structure 302 may be applied to a container when it is still a flat blank.

With reference to Figures 22a-d, use of the reclosable outlet forming structure 300 will now be shown and described. With reference to Figure 22a, prior to shipping of the container 302, the cap 310 may be placed over the outlet forming structure base 330 prior to removal of the breakaway tip 340 so as to assure that the breakaway tip 340 does not accidentally break and the

contents of container 302 do not escape while the container 302 is in transit. With reference to Figure 23b, the cap 310 is removed from base 330 to provide access to breakaway tip 340. The container at this point is ready for opening. With reference to Figure 23c, the breakaway tip 340 is then removed to create an opening 350. Opening 350 leads to a hole (not shown) in container 302 to allow pouring the contents of container 302 therethrough. With reference to FIG. 23a, the reclosable outlet forming structure 300 may be resealed by simply placing the cap 310 over base 330.

In one embodiment of the present invention, base 330 and tip 340 are cylindrical or substantially cylindrical, although it is to be understood that other shapes may be used. In this embodiment, the opening 350 is made of PET-PVC-BAREX. It is to be understood, however, that other materials in accordance with the present invention may be used.

As can be seen in Fig. 22d, the cylindrical outlet 330 and opening 350 act a nozzle direct the flow of the contents of the container 302 into a control stream.

With reference to Figures 23-26, a low profile breakaway tip and cap in accordance with another embodiment of the present invention is shown. In general, lowering the height of a breakaway tip 360 will lower the possibility that the tip 360 may be accidentally opened during transit or by handling. Lowering the height of the breakaway tip makes it more difficult, however, to grasp and remove the breakaway tip. This difficulty is alleviated by creating undercuts or indents 370 in the sidewall of the breakaway tip 360. These undercuts or indents 370 allows a user's finger to hook and break away the tip 360 in a single motion. Figure 25 is a perspective view of the low profile breakaway tip with the removed breakaway tip shown in phantom. With continuing

reference to Figures 23-25, the undercuts or indents 370 are preferably arranged in opposed positions to facilitate ease of use and manufacture. It is to be understood that the number and location of the undercuts/indents 370 may be varied. Once the breakaway tip 360 is removed from base 380, a cap 394 may be used to reclose the opening (not shown) exposed by the removal of tip 360 in base 390. Base indents 392 in base 380 are shaped and dimensioned to receive opposed inward protrusions 396 of cap 394. These protrusions 394 snap into indents 392, thereby securing cap 390 to base 380. A tether (not shown) may also be used to attach cap 390 to base 380.

As shown in Figs. 23a and 24a, the base 390a may have generally triangular cross-sectional area. Such a cross-sectional area, may aid in the dispensing of various materials. Furthermore, the relatively large bottom of the base 390a helps avoid accidental toppling of a container.

It is also to be understood that this embodiment of the present invention may be used in a wide variety of applications, including dispensers for creamers, unit dose medications, salad dressings, beauty aids, dental products, condiments, candy confections, syrups, granular products, etc. It is also to be understood that this embodiment of the present invention may be manufactured by utilizing a male punch member in conjunction with a self-centering and receding female anvil system, as previously shown and described.

Although the use of a tether limits the rotation of a cap pressed onto a base formation, a twist-lock or twist-threading arrangement may also be used to secure the cap to the base. With reference to Figure 28, such an embodiment of the present invention which utilizes a twist-lock or twist-threading arrangement 400 to secure the cap 410 to the base formation 420 is shown. In this

arrangement, cap 410 has an inner protrusion 415 which engages cam surface 430 of base 420. Upon rotation of cap 410 with respect to base 420, inner protrusion 415 engages cam surface 430 to create a twist-lock or twist-thread arrangement. It is to be understood that a tether (not shown) may also be used in such an arrangement. Base 420 may also have a breakaway tip 425 attached thereto.

As an alternative to the breakaway tip and tethered cap arrangement, the present invention also includes a tethered plug/punch and scored surface arrangement as shown in Figures 28a-c, 29a-d and 30a-d. Figures 28a and 28b are perspective views of such an embodiment of the present invention in which a tethered plug is used to open and close a pre-scored surface. In this arrangement 450, a plug 460 is used to open a pre-scored surface 470 of outlet 480. In this embodiment, the score is in the form of an interrupted circle, although it is to be understood that other types of scored surfaces, such as those shown in Figures 29a-d, may also be used. Figures 28b and 28c depict a flap 485 which is created when plug 460 is used to penetrate the scored surface 470. A tether 490 may also be created through the use of a score 495 in arrangement 450. Plug 460, which may be connected to arrangement 450 via this tether 490, may also be used as a cork to close the outlet hole. As such, plug 460 may be used both as a plug and as an opening tool to create and/or plug an aperture in the pre-scored surface. In this embodiment, plug 460 has a conical shape, although it is to be understood that other shapes may be used. Similarly, as shown in Figures 28a and 29a-d, the score may have a partially circular shape, a V-shape, an X-shape, a star shape, or box shape, although it is to be understood that other patterns may also be utilized. Depending on the shape of the scored surface, the flap created by the penetration of plug 460 will

differ. For example, the penetration of scored V-shaped surface 490 will create a flap 491; the penetration of scored X-shaped surface 492 will create a flap 493; the penetration of scored star-shaped surface 494 will create a flap 495; and the penetration of a scored surface 496 will create a rectangular-shaped flap 497.

An alternative embodiment of the present invention will now be discussed with reference to Figs. 31-36. In accordance with this alternative embodiment, a container 500 is provided with a reclosable outlet forming structure 510. More specifically, the outlet former structure 510 comprises a curvilinear dome or mound 530 and a dual purpose punch/plug 520. As will be apparent to one of skill in the art, the container 500 includes a hole, not shown, over which the mound 530 is secured. Because the punch/plug 520 must be lifted and inverted for insertion into the scored area 532, it must not be sealed to the container 500. On the other hand, the mound 530 portion of the outlet forming structure 510 must be securely adhered over the hole in the container 500.

As can best be seen in Fig. 34, the outlet forming structure 510 comprises a layer of foil 534 laminated to the plastic forming the outlet forming structure 510. The portion of the foil 534 underneath the mound 530 should be unsupported other than the adhesive used to secure it to the mound 530. It should also be noted that the foil 534 is secured to the container 500, about the hole in the container 500, so that the contents do not leak out beneath the outlet forming structure 510. The foil laminated adhesive should be one that gives adequate adhesion but sets up with minimal tensile strength of its own. In alternative embodiments, the adhesive may approach being brittle.

The mound 530 further includes a fault line pattern or scored pattern 532. The fault lines 532 may



take on any number of patterns, such as those shown in Figs. 29a-d. As shown in Figs. 35 and 36, the foil 534 is laminated to the entire surface of the mound 530 and preferably, is not scored. In an alternative embodiment, the adhesive may be omitted from the fault line pattern 532.

The punch/plug 520 is secured to the outlet forming structure 510 via a tether 524. The tether 524 is created by a cut 522 through the foil/plastic laminate. As can best be seen in Fig. 32, the cut 522 preferably takes a curvilinear path, following the periphery of the outlet forming structure 510. Such a cut 522 provides an elongated tether 524.

In operation, the punch/plug 520 is firmly pushed into the fault line pattern 532 to rupture the scored mound 530. This operation is best shown in Fig. 35. Having forced the punch/plug 520 through the scored area 532 of the mound 530, an opening for dispensing the contents of the container 500 is formed. The punch/plug 520 is removed from the mound 530 so that contents of the container 500 may be dispensed. Because the scored area 532 has been deformed to the shape of the punch/plug 520, the punch/plug 520 may be reinserted into the scored area 532, thereby resealing the container 500.

In an alternative embodiment, however, the foil layer 534 may span the hollow base of the mound 530 by being laminated only to the periphery of the mound. Of course, in such an embodiment, the punch/plug 520 must be long enough to extend past the plane of the foil 534 so that the foil 534 may be punctured. By wobbling the punch/plug 520 while inserted into the mound 530, the opening in the foil is enlarged.

It should be noted that the mound 530 strengthens the outlet forming structure 510. Furthermore, the shape of the mound 530 provides a nozzle

function, directing the contents of the container 500 in an even stream. Depending upon the contents of the container 500, the dimensions and shape of the mound 530 may be altered to provide the desired flow.

5           The outlet forming structure 510 of Figs. 31-36 are preferably manufactured with a punch similar to that described with reference to Fig. 12b. Of course, the tip of the punch need not be spherical, but rather may be elliptical, parabolic, or any curvilinear shape.  
10       Furthermore, it is preferred that the foil and plastic be laminated into a single web prior to the formation of the mound by the punch. Thus, the dimensions of the mound, as defined by the shape of the punch tip, will be limited only by the physical properties of the materials used.

15           In an alternative embodiment, which will now be described with reference to Figs. 37-38, a reclosable outlet forming structure 610 according to the present invention is utilized with a flexible plasti-foil pouch 600. In general, the foil pouch 600 is formed by folding  
20       a generally rectangular shaped piece of the foil plastic combination in half and sealing the three open edges thereof. A reclosable outlet forming structure 610 is mounted on the seamless end 605 of the pouch 600. The outlet forming structure 610, which is sealed to the  
25       seamless end of the pouch 600 by applying an adhesive around a periphery of the base 612, covers a hole, not shown, in the pouch 600.

30           The outlet forming structure 610 may be of any type previously disclosed above, such as those described with reference to Figs. 1-3, 8-9, 13, and 13a. In a preferred embodiment, as shown in Figs. 37 and 38, the outlet forming structure 610 includes an aperture forming protrusion 630. More specifically, the aperture forming protrusion 630 includes a hollow cylindrical base 632 and  
35       a break-away tip 634. A fault line 636 extends around the

periphery of the protrusion structure 630, permitting the breakaway tips 634 to be broken away from the base 632 in the tip 634. More specifically, the fault line 636 is a narrowed, stress concentrating area.

5           The outlet forming structure 610 also includes a cap 620. The cap 620 is a hollow tapered member, which has an inside base diameter slightly larger than the outside diameter of the base 632 of the protrusion structure 630. The cap 620 is secured to the outlet  
10   forming structure 610 via a tether 624. The tether 624 is formed by a cut 622 through the lower surface 612 of the outlet forming structure 610. As can best be seen in Fig. 39, the curvilinear cut 622 separates the cap 620 from the protrusion structure 630 and follows the periphery of the  
15   base 612. By having such a pattern, the cut 622 is relatively long and, consequently, produces a relatively long tether 624. Due to the long tether 624 and the fact that the portion of the base 612 that supports the cap 620 is not fastened to the pouch 600, the cap 620 may be  
20   raised and securely placed over the outlet forming structure 630.

          In operation, a user applies sidewise finger pressure to the protrusion tip 634, thereby causing it to break away from the protrusion base 632 along a fault line  
25   636. Because the protrusion structure 630 is substantially hollow, an aperture, not shown, is created. Furthermore, because the protrusion member 630 has been affixed to the pouch 600 over a hole in the pouch, not shown, the contents of the pouch 600 may be dispensed via  
30   the now opened protrusion neck 632. The cap 620 is placed over the base 632 during shipping, so that accidental rupturing of the fault line 636 is prevented. Furthermore, cap 620 is placed over the base 632 to reclose the package 600 when only a portion of the  
35   contents of the package 600 has been dispensed.

In an alternative embodiment, shown in Fig. 39, the same outlet forming structure 610 is secured to the side of pouch 640. In this embodiment, the pouch 640 is formed from two generally rectangular sheets of foil plastic laminate which are sealed together around all four sides of each sheet. As with the previous embodiment, the protrusion structure 630 is affixed to the pouch 640 over a hole, not shown, so the protrusion neck 632 is in fluid communication with the contents of the pouch 640.

An alternative embodiment of the present invention employing an outlet forming structure 610a disposed on a foil pouch 640a will now be described with reference to Figures 37a, 38a, and 39a. Briefly described, the outlet forming structure 610a is substantial the same as the outlet forming structure described with reference to Figures 37-39. Specifically, the outlet forming structure 610a includes both a cap 620a and a protrusion member 630a. As best seen in Figure 39a, the foil pouch 640a includes a lap seam on the side opposite the outlet forming structure 610a.

An alternative embodiment of the present invention will now be described with reference to Fig. 40. A tethered punch/plug and base member with a star shaped fault pattern manufactured as a unit 700 is shown. A tether 730 is connected to the base 710 at a proximal end thereof, a ring structure 740 connected to a distal end thereof, and a tapered punch/plug 760. The punch/plug 760 is manufactured separately from the other components.

As shown, the ring structure 740 defines an opening 750. The opening 750 is larger than the tip 762 of the punch/plug 760 yet smaller than the base 764 of the punch/plug 760. Furthermore, the punch/plug 760 includes a circumferential indentation 766. The indentation 766 is formed on the punch/plug 760 just below a point where the

outside diameter of the punch/plug 760 becomes larger than the inside diameter of the opening 750.

Therefore, once the components have been separately manufactured, the punch/plug 760 is snapped into the opening 750. When snapped into the opening 750, the tapered punch/plug 760 causes the slightly elastic ring structure 740 to expand until the ring structure 740 reaches the indentation 766. Upon reaching the indentation 766, the ring structure 740 snaps into the indentation 766. Consequently, the punch/plug 760 becomes connected to the ring structure 740 and the other components.

In use, as shown in Figure 40a, the punch/plug 760 is used to puncture the scored section 722 of the protrusion structure 720. Such operation is described in greater detail with reference to Figs. 28-30d.

Turning now to Fig. 41, one embodiment for manufacturing a reclosable outlet forming structure according to the present invention is shown. Specifically, a pair of reclosable outlet forming structures 870 and 880 are formed from the same piece of thermoplastic web F. Each reclosable outlet forming structure 870, 880 comprises a protrusion structure 872, 882 as well as cap 874, 884, respectively. As in the previously disclosed embodiments, each cap 874, 884 is connected to the corresponding protruding structure 870, 880 via a tether 876, 886.

It is to be understood that the mating, horse-shoe arrangement of the outlet forming structures 870, 880 provides several benefits, such as reclining wasted portions of the web F, and that the manufacturing agreement may be repeated along the length of the web F.

Turning now to Figures 42-44, an alternative embodiment of the present invention is shown. Initially, it should be noted that the container 1000 shown is made

of similar materials as described above with reference to Figure 1-3.

5 The container 1000 comprises a first deformable pouch 1010 and a second deformable 1020. The two pouches 1010, 1020 are joined by a shallow conduit 1030. The deformable pouches 1010, 1020, as well as the joining conduit 1030, are sealed by a generally flat sheet 1040 of thermoformable plastic material. A hollow protrusion 1050 is integrally formed with the flat sheet of thermoformable plastic 1040. The hollow protrusion 1050 extends from the flat sheet 1040. The protrusion 1050 is directly above and in fluid communication with the conduit 1030. The container 1000 further includes a punch/cap 1060.

10 As can best be seen in Figure 43, the hollow protrusion 1050 has scores or fault lines 1055 on the top face thereof. Despite these fault lines 1055, which weaken the protrusion 1050, the container 1000 remains sealed. Further shown in Figure 46, the punch/cap 1060 is partially separated from the remainder of the container 1000 by cut 1062. The cut 1062 which parallels one peripheral edge of the container 1000 creates a tether 1064.

15 In order to open the container 1000, the punch/cap 1060 is positioned over the protrusion 1050. The punch/cap 1060, and more specifically the pointed end 1066 of the punch/cap 1060 is forced through the score or fault lines 1055, thereby opening the hollow protrusion 1050. When punch/cap 1060 is removed from the hollow protrusion 1050, an opening, not shown, exists. The opening is formed by the permanent deformation of the portion of the protrusion member 1050 between the fault lines 1055. By inverting the container 1000 and gently squeezing either or both of the pouches 1010, 1020 the material contained within the pouches is dispensed via the opening in the protrusion 1050.

It should be noted that in the preferred embodiment the protrusion 1050 is placed directly above the conduit 1030. As a result, the contents of the pouches 1010, 1020 can be dispensed in a controlled manner. Specifically, the shallow conduit 1030 provides resistance to the flowing contents so that the contents do not spout from the opened protrusion 1050 uncontrollably, particularly when the protrusion 1050 is initially punctured.

As shown in Figure 44, should less than all of the material contained within the pouch 1010, 1020 be dispensed, the container 1000 may be reclosed. Specifically, the punch/cap 1060 is inverted by twisting the tether 1064. Because the punch/cap 1060 is hollow, having an inside diameter substantially the same as or slightly larger than the outside diameter of the protrusion 1050, the punch/cap 1060 can be securely placed on the protrusion 1050.

With regard to the embodiment of Figures 42-44, it will be apparent to one skilled in the art that the invention is not limited by the type of outlet forming structure utilized. Specifically, any combination of break away tip, scored protrusion member, punch, plug, and cap may be employed. Furthermore, it should be understood that the particular shape of the pouches may vary according to the properties of the contents held therein.

An alternative embodiment of the present invention will now be described with reference to Figures 45-47. As shown in Figure 45, an outlet forming structure 1070 comprises a cap member 1072 and an aperture forming protrusion 1074. As with the embodiments discussed above, the cap member 1072 is connected to the aperture forming structure 1074 by a tether 1076. As can be seen, both the cap member 1072 and the aperture forming structure 1074 are formed in a curvilinear base 1078.

Because the outlet forming structure 1070 is formed in a curvilinear base 1078, it may be positioned on a container 1080 having a similar curvilinear surface. As shown in Figures 46a-c, one such container 1080 is generally spherical and formed in two halves 1082, 1084. The two halves 1082, 1084 are joined at one point along their circumferences, and are therefore hingeably connected. One half 1084 of the container 1080 includes an aperture 1086 formed therein.

In operation, as shown in Figure 47, the outlet forming structure 1070 is affixed to the container 1080 such that the aperture forming structure 1074 is in alignment with the aperture 1086 in the container 1080. As further depicted in Figure 47, the cap member 1072, shown in a sectional view, may be positioned over the aperture forming structure 1074, thereby protecting it and sealing the container 180. It is to be understood that the shape of the container 1080 is merely representative of those that may be employed with the present invention, as the outlet forming structure may be formed on a curvilinear base having virtually any shape.

Another alternative embodiment of the present invention will now be described with reference to Figures 48-51. The container 1090 generally comprises a rectangular sheet 1091 of thermoformable material. At the center of the rectangular sheet 1091 is an aperture forming structure 1092, having a base and break away tip as described above with reference to the prior embodiments. On either side of the aperture forming structure 1092 are pouches 1098 formed on the underside of the sheet 1091 for holding any flowable substance. The pouches 1098 are in fluid communication with the aperture forming structure 1092.

Also formed in the rectangular sheet 1091 of thermoformable material is a cap member 1094. The cap



member 1094 is preferably formed in one corner of the rectangular sheet 1091 and attached to the container 1090 via a tether 1096. The tether 1096 is formed by a cut 1097 extending along the perimeter of the container 1090.

5           The container 1090 may be folded generally in half along bending grooves 2006 disposed on either side of the aperture forming structure 1092. Specifically, the ends of the container 1090 are brought together as depicted by arrows "A" in Figure 49. Once the ends are  
10 brought together, a female package tie 2000 and a male package tie 2002, both of which are integrally formed in the sheet of thermoformable material 1091, are brought into engagement.

15           Engagement of the female package tie 2000 and the male package tie 2002 hold the container 1090 in the configuration as shown in Figures 50 and 51. In operation, lateral finger pressure on the tip of the aperture forming structure 1092 causes a fault line to rupture, thereby forming an aperture in the aperture  
20 forming structure 1092. Thus, the contents of the container 1090 may be dispensed from the aperture. As shown in Figure 51, the cap member 1094 may be placed over the aperture forming structure 1092, thereby preventing accidental rupturing of the fault line or accidental  
25 dispensing of the contents after the tip of the aperture forming structure 1092 has been removed.

30           Another alternative embodiment of the present invention will now be described with reference to Figures 52-54. As shown in Figure 52, an aperture forming structure 2016 according to the present invention may be positioned on a treated paper board tube 2012, thereby forming a sealed container 2010. The aperture forming structure 2016 comprises a generally hollow frusto-conical portion 2018, a hollow cylindrical portion 2019, and a  
35 breakaway tip 2020. Integrally formed with the aperture

forming structure 2016 is a cap member 2022 and an  
associated tether 2024. As can best be seen in Figure 54,  
the tether 2024 is formed by a curvilinear cut which  
allows the cap member 2022 to be partially separated from  
the aperture forming structure 2016 so that the cap member  
2022 may be positioned over the cylindrical portion 2019  
and the breakaway tip 2020. Because the cap member 2022  
has an inside diameter slightly larger than the outside  
diameter of the cylindrical portion 2019, the cap member  
2022 fits snugly thereon, thereby sealing the container  
2010.

As with the previously described embodiments, in  
operation, lateral pressure on the breakaway tip 2020  
causes it to separate from the rest of the aperture  
forming structure 2016, thereby forming an aperture into  
the generally hollow aperture forming structure 2016.  
Thus, the contents of the container 2010 may be dispensed  
therefrom.

It will remain understood by those skilled in  
the art that the present invention in its broader aspects  
is not limited to the particular embodiments shown and  
described herein, and that variations may be made without  
departing from the principles of the invention and without  
sacrificing its chief advantages.